



Outdoor Enclosure by Kam Fabrication

291SL

Specifications

- **Weight**
3.04 lbs
- **Overall Height**
14 3/16" H x 9 1/8" W x 3 5/8" D
- **Inside Height**
11 15/16" H x 6 15/16" W x 3 1/2" D

Features and Benefits:

- New thumb screw design, Creates better gasket contact
- 291 cubic inch hinged enclosure
- Made from all aluminum and stainless steel
- Made from the thinnest materials possible to reduce weight, perfect for tower applications
- This enclosure is designed for NEMA 4X specifications
- This new design has no rivets and no steel hardware, so no rusting!
- Comes with pre-punched sub plate and stand offs to mount circuit board
- Sub plate is printed for both Mikrotik and Ubiquiti boards
- The 291SL will accept an 800 with an 816 Daughterboard
- There is a mounting location inside the enclosure for a DBI safe surge
- 3 antennae KO's on top, 4 antennae KO's on bottom, and 1 Ethernet
- Enclosure is lockable
- New, all thumb screw design allows for tool less entry and provides maximum seal with rubber gasket
- New hard point mounting locations on rear, allows for optional accessories
- Comes standard with wall mount/hose clamp bracket and 2 all stainless steel hose clamps, with range of 46-70mm
- Powder coated Sky White