

QuPS4

Outdoor power socket & plug - 4 PIN set

Outdoor power socket & plug 4 PIN set for all cases where the user doesn't want to use Passive PoE powering feature in all QuWireless antennas.





(MECHANICAL SPECIFICATION

MAXIMUM CURRENT

5A

MAXIMUM VOLTAGE

200V

TEMPERATURE RANGE

-25...70°C

MINIMUM MATING CYCLE

500x

MINIMUM MATING CYCLE FOR MOLEX CONNECTOR

250x

INGRESS PROTECTION

IP68

CONNECTOR TYPE

SP1310/P4I-N, 4 pin Micro-Fit 3.0, 4 pin (2x2)

SP1310 CONNECTOR MATERIALS

Internal contacts material: Brass Internal contact finishing: Gold

MICRO-FIT 3.0 CONNECTOR MATERIALS

Internal contacts material: Phosphor bronze Internal contact finishing: Tin

CABLE TYPE

H05VV-F (OWY) 300/500V 4 cores 0,5mm², stranded wire, diameter 8mm, length 150mm

CONNECTOR PINOUT

- 1 Power (+)
- 2 GND (-)
- 3 Data Input
- 4 Data Output

CONNECTOR FLAMMABILITY CLASS

UL94V-O flammability class of plastic housing



ROHS COMPLIANCE

Directive 2011/65/EU Directive 2015/863

WEIGHT

0,023 kg 0.051 lbs



WWW.QUWIRELESS.COM

Sales email: sales@quwireless.com Tel: +48 513 900 416

Support email: support@quwireless.com **Website:** www.quwireless.com

Address: Wireless Instruments Sp. z o.o., ul. Kościuszki 27, 52-116 Iwiny, Poland



