



MA-WA55-TPMIMO

5.125-6.1 GHz Triple Polarization MIMO Subscriber Antenna

MARS Triple Polarization antenna provides coverage of 5.125-6.1 GHz frequency band in a single antenna radome.

Additional Features:

- 3 Ports: Dual Slant (±45°) and Vertical Polarization.
- Specially designed for MIMO applications for optimal decorrelation.
- Light weight and durable construction.
- UV protected radome made of polycarbonate.
- Can be customized with customer defined back plane and different connector configurations.

Specifications

Electrical			
Frequency range		5.125-6.1 GHz	
GAIN	Vertical Pol.	19 dBi	
	Dual Slant Pol.	17.5 dBi	
VSWR, max.		1.7 : 1	
Polarization		Dual Slant ± 45° and Vertical	
3 dB Beam-Width-Azimuth, typ.		Dual Slant: 20°; V- Pol 22°	
3 dB Beam-Width-Elevation, typ.		Dual Slant: 19°; V- Pol 14°	
Side Lobes, min.		-12 dB	
Front to Back Ratio, min.		-35 dB	
Port to Port Isolation		-40 dB (Vertical to ±45° Dual Slant)	
Port to Port Isolation		-30 dB (+45° Dual Slant to -45° Dual Slant)	
Input power, max.		10 Watt	
Input Impedance		50 Ohm	
Lightning Protection		DC Grounded	
Mechanical			
Dimensions (HxWxD)		305 x 305 x 15 mm (12" x 12" x 0.6")	
Connector		3 x N-Type Female	
Weight		1.5 kg.	
Mounting		See ordering options	
Radome		UV Protected Polycarbonate	
Back Plane		Aluminum protected through chemical passivation	
Environmental			
Operating Temperature Range		-55°C to +65°C	
Vibration		According to IEC 60721-3-4	
Wind Load		200 Km/h (Survival)	
Flammability		UL94	
Water Proofing		IP-67	
Humidity		ETS 300 019-1-4,EN 302 085 (Annex A.1.1)	
Salt Fog		According to IEC 68-2-11	

Ordering Options		
MA-WA55-TPMIMO	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)	
MA-WA55-TPMIMOB	Antenna with MNT-22 mount	

Patterns are available on our website

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

