

MA-WO56-DP10

4.9-5.9 GHz Dual Polarization Omni Directional Antenna

MARS 4.9-5.9GHz Dual Polarization Omni Directional Antenna provides a cost effective solution for large scale WLL, WLAN, ISM and Point-to-Multi Point applications.

UV protected radome suitable for harsh environment installations.

Antenna features stable performance with exceptional 10 dBi of gain.

Applications:

- MESH Networks.
- Point-to-Point Applications.



Specifications

Electrical

Frequency range	4.9 - 5.9 GHz
GAIN, typ.	4.9-5.1 GHz Vertical @ 8dBi & Horizontal @ 10dBi 5.1-5.9 GHz Vertical & Horizontal @ 10dBi
VSWR, 1.7 : 1 typ.	4.9-5.1 @ 2.5:1 max. 5.1-5.9 @ 2: 1 max.
Polarization Dual Pole	Vertical & Horizontal
3 dB Beam-Width, Azimuth, typ.	Omni - Directional
3 dB Beam-Width, Elevation, typ.	11°
Port to Port Isolation	-30 dB typ. -20 dB min.
Input power, max.	10 Watt
Lightning Protection	DC Grounded
Input Impedance	50 Ohm

Mechanical

Dimensions (HxDia.)	355 x 66 mm
Weight	370 gr.
Connector	2 X N-Type, Female
Radome	UV Protected Polycarbonate
Mount	2" Pole Mount

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com