



global solutions :
local support™

Mesh Series™ Vertically Polarized Omni 2.4GHz to 5.85GHz

The Mesh Series™ omnidirectional antenna systems offered by Laird Technologies are designed with mesh networking in mind. With their waterproof N male connector they can be easily mounted to an enclosure like the Laird Technologies Die Cast Enclosure (DCE-7x6x2) to give total wireless coverage. Various gains and frequencies are available. They are constructed of UV resistant materials and are waterproof for a long service life.

Features and Benefits:

- Mesh networking vertically polarized omnidirectionals
- Various gains available: 5dBi to 12dBi
- Various frequencies available: 2.4GHz 3.5GHz, 4.9GHz, 5GHz, also Tri-Band Model
- Type N male integrated connector
- Rugged, lightweight and waterproof

Applications


- Mesh networking applications
- 2 to 6 GHz wireless applications
- Point to multi-point systems
- Base station antennas
- WiFi access points
- WiMax base stations

For sales information:

Telephone 801-572-3024

E-Mail sales@pacwireless.com

or visit: www.pacwireless.com




Specifications

Parameter	Min	Typ	Max	Units	
VSWR		1.5:1			
Impedance		50		OHM	
Input Power			10	W	
Rated Wind Velocity			125 (56)	mph (m/sec)	
Operating Temperature	-40		+70	Deg C	


Model	Freq. (MHz)	Gain	Vert BW	Weight	Dim (L x dia)
OD24M-5	2400-2485	5dBi	25 deg	0.5 lbs (0.2kg)	12x0.6" (355x15mm)
OD24M-7	2400-2485	7dBi	18 deg	0.6 lbs (0.3kg)	21x0.6" (540x15mm)
OD24M-9	2400-2485	9dBi	14 deg	0.8 Lbs (0.4kg)	27x0.6" (690x15mm)
OD24M-12	2400-2485	12dBi	7 deg	1.4 Lbs (0.6kg)	48x0.6" (1220x15mm)
OD35M-10	3400-3600	10dBi	14 deg	1.1 Lbs (0.5kg)	27x0.6" (690x15mm)
OD49M-6	4940-4990	6dBi	30 deg	1.5oz (43g)	7x 0.5" (175x13mm)
OD49M-11	4940-4990	11dBi	5 deg	1.1 Lbs (0.5kg)	31x0.6" (787x15mm)
OD5WM-6	5150-5850	6dBi	8.5 deg	5oz (0.14kg)	19x0.6" (483x15mm)
OD58M-12	5400-5850	12dBi	7 deg	.65 Lbs (0.5kg)	27.5x0.6" (700x15mm)
RD2458-5-NM	2400-2485, 5150-5350, 5725-5850	2dBi@2.4 5dBi@5.8	120 deg	1.6oz (45.4g)	7.6x0.5" (193 x 12.7mm)

Antenna Patterns




OD24M-5 E-Plane

OD24M-7 E-Plane




OD24M-9 E-Plane

OD24M-12 E-Plane



OD49M-11D1 E-Plane


OD49M-6 E-Plane



OD58M-12

OD5WM-6

System Ordering:



24 = 2400 to 2485MHz
 35 = 3400 to 3600 MHz
 49 = 4940 to 4990 MHz
 58 = 5400 to 5858 MHz
 5W = 5150 to 5850 MHz

5 = 5dBi
 12 = 12dBi
 etc.

Notes:

- All shipments F.O.B. Schaumburg, IL 60173
- All antennas carry a 2 Year Warranty

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

Specifications subject to change without notice.

