

AU POWER SUPPLY 24W



TECHNICAL DATA

GENERAL

| | |
|------------------|------------------|
| Input voltage | 100 - 240 VAC |
| Input frequency | 50/60 Hz |
| Input current | 0.8 A |
| Input connector | AU (Type I) |
| Output voltage | 12 VDC |
| Output current | 2.0 A |
| Output connector | 4pin, 3 mm pitch |
| Weight | 115 g |

ADDITIONAL

| | |
|-----------------------------------|--------------------------------|
| Input voltage absolute maximum | 90 - 264 VAC |
| Input frequency absolute maximum | 47 - 63 Hz |
| Inrush current | 60 A |
| Output voltage absolute maximum | ± 0.6 VDC |
| Short circuit protection | ✓ |
| HIPOT (dielectric withstand test) | Primary to Secondary: 4000 VDC |
| MTBF | 30000 h |
| PSU efficiency standard | DoE Level VI |

Safety: AS/NZS 60950.1:2015
 AS/NZS 60065:2012 Inc A1
EMC: AS/NZS CISPR 22:2009+A1:2010
 AS/NZS CISPR 13:2012
 EN 55032:2012
 EN 55024:2010
 EN 55020:2007+A11
 EN 61000-3-2:2014
 EN 61000-3-3:2013

Certification

