



GVC3200
Grandstream GVC3200 Full HD Video Camera
Conferencing System

Bands

2.4GHz , 5.0GHz

Wireless Standards

802.11a , 802.11b , 802.11g , 802.11n , Bluetooth

Ethernet Speed

1Gbps

Stock Level: Product in stock

~~\$4,682.00~~ \$2,795.00 + GST

Description

The Grandstream GVC3200 is a ground-breaking solution that offers businesses a revolutionary IP video conferencing system with unprecedented flexibility and the power of support for multiple popular video conferencing protocols and platforms right out of the box. The SIP-based GVC3200 supports Grandstream’s robust [IPVideoTalk](#) platform for plug and play video conferencing while also being interoperable with any 3rd party SIP video conferencing platform - thus offering a great option to expand or implement a 3rd party platform. Additionally, the GVC is based on Android 4.4 and therefore offers full access to all video conferencing apps in the Google Play Store. The GVC3200 sports an innovative, patent-pending embedded MCU that supports up to 9-way video conferencing with local mixing between SIP and other protocols.

[Checkout the IPVideoTalk Learning Centre to see how easy and flexible the GVC and IPVideoTalk can be!](#)

Features

- Supports any SIP platform and any Android app - and can bridge calls from Android apps into SIP conference
- Built-in Bluetooth for use with Bluetooth speakers/microphones, keyboards, data exchange, etc
- Support for 3 screens thanks to 3 HDMI outputs
- Experience video resolutions up to 1080p and 12x optical zoom!
- Gigabit Ethernet and Dual-band WiFi support offers exceptional speed and mobility
- Share a presentation with conference attendees or review a document
- Easily record all video conferences to document meetings
- The GVC3200 can remind attendees 10 mn before start-time and automatically call all participants

Specifications

Details

| | |
|-----------------------------|---|
| Manufacturer's Product Code | GVC3200 |
| Protocols/Standards | SIP RFC3261, BFCP, TIP (pending), RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, LLDP-MED, LDAP (pending), TR-069, 802.1x, TLS, SRTP, TCP/IP/UDP, IPv6 (pending), FEC, FECC, (pending: H.323, H.245, H.225, H.235, H.241, H.460) |
| Camera | 1/3" 2 Megapixel CMOS 1920Hx1080V @30fps |
| Lens | 12x optical zoom, +/-23° tilt, +/- 90° pan, 70°(W)*- 6.3° (T) field of view |
| Network Interface | 1x RJ45 10/ 100/ 1000 Mbps port |
| Wi-Fi | Yes, integrated dual-band 802.11 a/b/g/n (2.4GHz & 5GHz) |

Details

| | |
|---------------------------------|--|
| Bluetooth | Yes, integrated. Bluetooth 4.0 + EDR |
| Video Outputs | 3x HDMI up to 1080p with CEC |
| Video Input | 1x VGA/1x HDMI with resolution up to 1080p |
| Microphone/Speaker | External MIC/Speaker, built-in MIC, cascadable external MIC/speaker (pending) |
| Remote Control | Bluetooth remote control with multi-touch touchpad |
| Auxiliary Ports | 1x USB 2.0, SD, external speaker port, reset pin |
| Graphic Display | OLED with 128x32 resolution |
| Voice Codecs | G.711µ/a, G.722 (wide-band), G.726-32, iLBC (pending), Opus, G.722.1, G.722.1c (pending), in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO) |
| Video Codecs | H.264 BP/MP/HP, video resolution up to 1080p, frame rate up to 30fps, bitrate up to 4Mbps |
| People Video Resolution | 1080p from 512 Kbps, 720p from 384 Kbps, 4SIF/4CIF from 128 Kbps, SIF/CIF/QSIF/QCIF/SQSIF/SQCIF from 64 Kbps |
| Content Video Resolution | Input: VGA, SVGA, XGA, WXGA, WXGA, SXGA, 1440x900, 720p, 1600x1200, 1080p (HDMI), up to 60fps; Encoding: 1280x720, 1920x1080 |
| Output Resolution | 720p, 1080p |
| Embedded MCU | Up to 4-way 1080p conference, 5-way 720p conference, 9-way VGA conference |
| Dual-Stream | BFCP, people video (up to 1080p@30fps) + content video (up to 1080p@15fps, 720p@30fps) |
| Audio Features | AEC, ANS, AGC, PLC, CNG/VAD |
| Video Features | FEC, dynamic display layout, picture-in-picture, picture-outside-picture, digital caption (pending) |
| Platform Bridging | Bridge SIP calls with any Android VoIP apps such as Google Hangouts and more |
| Telephony Features | Hold, transfer, forward (unconditional/no-answer/busy), call park/pickup, 9-way audio/video conference, downloadable XML phone book, LDAP (pending), call waiting, call history, flexible dial plan, personalized music ringtones, server redundancy & fail-over |
| Sample Applications | Google Hangouts, Web browser, Facebook, Twitter, YouTube, Google calendar, mobile phone data import/export via Bluetooth, etc. API/SDK available for advanced custom application development |
| Application Deployment | Allows Android 4.4.2 compliant applications to be deployed in the device with provisioning control |
| QoS | Layer 2 QoS (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ, MPLS) QoS |
| Security | User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, 128/256-bit SRTP, HTTPS, 802.1x media access control |
| Upgrade/Provisioning | Firmware upgrade via TFTP / HTTP / HTTPS or local HTTP upload, mass provisioning using TR-069 or AES encrypted XML configuration file |
| Power & Green Energy Efficiency | Universal power adapter included: Input 100-240VAC 50-60Hz; Output 12VDC/5A (60W) |

Resources

Firmware & Downloads

[FAQs](#)

[Tools](#)

[Forums](#)

Details

| | |
|----------------|--|
| Power Supply | (1) 12VDC/5A PSU |
| Devices | (1) GVC3200, (1) GAC2500, (1) Remote Control including (2) AAA batteries |
| Cables | (1) External USB speaker/MIC, (1) USB extension cable (5 meters), (4) HDMI cables (one 1.5 meter cable, two 3 meter cable and one 5 meter cable) |
| Ethernet Cable | (1) Patch Cable 1.5m |
| Mounting | (1) Wall Mounting Kit |